

**Gysflash 30-24 HF is a high power stabilised supply (30A-12V & 15A-24V) incorporating Inverter technology with 5 functions :**

- **Battery support:** sustains 6, 12 and 24V (liquid or gel) automotive battery during diagnostic work
- **Advance battery charger:** ensures an ideal charging cycle for battery maintenance for the most modern vehicle
- **Showroom mode:** maintains batteries in showroom vehicles
- **In «battery change» mode,** will maintain electrical supply to preserve vehicle memory settings
- **High power stabilised supply:** voltage & current adjustable

## 5 Modes

- Charge
- Diagnostic
- Showroom
- Change batterie
- Power Supply

## Advanced features

- Automatic restart
- Cable test and calibration
- Showroom mode lock
- "Easy charge" mode
- Activate and adjust an "expert" charging curve
- Automatic SOS recovery for sulphated battery



## Intuitive interface

19 Languages available

## Slim size

The height of the charger (<11cm) enables to place it under vehicle

## Cables

- Fitted with 2x2.5m - 6mm<sup>2</sup> cables
- It can be fitted with 2x5m - 16mm<sup>2</sup> and more. The calibration is automatic.

## TECHNOLOGY

High duty cycle

**94%**

15% more energy




No external ventilation  
= No dust ingress



**Inverter - This technology enables :**

- A better duty cycle for a light weight (3.8kg).
- Shock and vibration absorbing feet.

## FEATURES



### Showroom Mode and reduced dimensions :

- Slim height (< 11 cm): to enable placement under vehicle.
- Showroom mode lock: to avoid mishandling ideal for garages and showrooms.
- Automatic restart: will automatically resume the mode from last position in case of power failure.

CE - EN 60335-2-29

50/60hz	500W	Imax 100% @40°C	6V	MIN. MAX. Ah	Laddar Kurva	BSU			Byta Batteri	IP	cm	kg	
						Diag	Diag +	Visningsrum					
230V	500W	30A	6V	10-400Ah	IU <sub>0</sub> I <sub>0</sub> U	13,5V	6>7.4V	6,5V	40A	IP 21	25,5x23x10,5	3,8	
			12V				12>14.8V						12,9V
			15A				24V						10-200Ah