

**Invaluable when the power source cannot be situated directly beside the welder, remote controls can help improve productivity and reduce welder fatigue.**

### Product compatibility

GYSARC 300 TRI  
 GYSARC 400 TRI  
 PROGYS 220E FV  
 PROGYS FLEX 280 CEL  
 EXAGON 400 CC/CV  
 EXAGON 400 FLEX CC/CV  
 PROTIG 221 DC FV  
 PROTIG 231 DC FV  
 PROTIG 231L DC FV  
 TITAN 231 DC FV  
 TIG 300 DC  
 TITAN 400 DC TRI  
 PROTIG 201 AC/DC FV  
 PROTIG 201L AC/DC  
 TITANIUM 230 AC/DC FV  
 TIG 250 AC/DC  
 TITANIUM 400 AC/DC TRI



### Compatible processes

MMA / TIG

### How it works

The foot pedal is used to control the current from minimum up to 100% of the current that is set on the machine.

In TIG, the power source only operates in 2T mode. Current rise and fade are no longer controlled by the power source (inactive functions) but rather by the operator using the foot pedal.

*Example:*

*The minimum current of the product is 5A. The welder has set the unit to 120A. Using the foot pedal, the current can be adjusted between 5A and 120A.*

### Cable length

4 m

### Accessories (optional extras)

7-pin male connector

045699

mm	kg		
228 x 160 x 110	1.4	4 m	7 pins